

Specification Sheet

Hook Loader

Series Hook Loader

Sheet: 1 of 1

Date: September 2009

Subject Technical Information & Data



Hook lift	Model					
	HL6	HL9	HL16-S	HL16	HL16-L	HL20
Lift capacity (t)	6	9	16	16	16	20
Bin length (m) max.	4.4	4.9	5.7	6.2	6.4	6.4
Bin length (m) min.	2.7	3.4	4	4.3	4.5	4.5
Bin runner OD (mm)	1060mm (opt. 700mm)	1060mm (opt. 870mm)	1060mm	1060mm	1060mm	1060mm
Bin pin height to bottom of pin (mm)	1130mm	1550mm	1565mm	1565mm	1565mm	1565mm
Bin runner height (mm)	125mm	150mm	180/200mm	180/200mm	180/200mm	180/200mm
Bin clamp lock onto runner (Std)	Inside	Inside	Inside	Inside	Inside	Inside
Vehicle GVM	10.5	15/16	24/25	24/25	24/25	32
Vehicle axle spec	4 x 2	4 x 2	6 x 4	6 x 4	6 x 4	8 x 4
Fitted mass (kg)	900 kg	1,250 kg	1985 kg	2005 kg	2025 kg	2190 kg
EXRA cab to rear axle (mm)	3040mm	3578mm	4325mm	4810mm	5040mm	5040mm
Indicative payload (t)	6	9 ~ 10	13.5 ~ 14.5	13.5 ~ 14.5	13.5 ~ 14.5	17
Hyd flow (LPM)	35	65	75	75	75	95
Hyd pressure (bar)	210	210	240	240	240	250
Standard configuration	In cab joy stick control, 3 flashing beacons, single container clamp lock system, rear bumper bar, two pac black finish.					
Options						
Telescopic hook	N/A	N/A	Yes	Yes	Yes	Yes
Articulated hook	N/A	Enquire	Yes	Yes	Yes	Yes
LED rear lights	Yes	Yes	Yes	Yes	Yes	Yes
Work light (each)	Yes	Yes	Yes	Yes	Yes	Yes
Dual clamp locks	Yes	Yes	Yes	Yes	Yes	Yes
Outside clamp lock	Yes	Yes	Yes	Yes	Yes	Yes
In cabin clamp lock status/warning lights	Yes	Yes	Yes	Yes	Yes	Yes
Toolbox (1000 x 450 x 450mm)	Yes	Yes	Yes	Yes	Yes	Yes
Tow bar and coupling	Yes	Yes	Yes	Yes	Yes	Yes